

Timed Ignitor 380/440+/-10% 50/60hz


Ignitor Code: PCT150485

Electrical Data (Ignitor)

Wattage (W)	1000-2000
Timed	Y
Ignitor Type	Superimposed
Max Lamp Current (A)	11
Pulse Magnitude (kV)	5.0-6.0
Max. Lead Capacitance (pF)	100
Max Case Temp (°C)	90
Internal Temp (°C)	25

Maximum distance between ignitor and lamp is shown as "Max. Lead capacitance (pF)" where approximately 100pF = 1 metre.

Physical Data (Ignitor)



Dimensions (mm)	Ø	L	
	60	93	
Fixing	M12x13		
Weight (kg)	0.51		

Notes:

Data is based upon tests performed by Venture Lighting in a controlled environment and is representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

Venture Lighting Australia

110 Lewis Road Wantirna South VIC 3152
 Ph: +61 3 9800 5600
 sales@venturelighting.com.au
 venturelighting.com.au

Venture Lighting New Zealand

Unit 1, 9 Orbit Drive Rosedale 0632
 Ph: +64 9 415 6332
 sales@adlt.co.nz
 venturelighting.co.nz

Venture Lighting Singapore

Ph: +65 6844 2338
 sales@adlt.com.sg
 venturelighting.com.sg